L Number	Hits	Search Text	DB	Time stamp
1	0	mounting near apparatus and blow\$2 same devices and 29/\$.ccls. and 414/\$.ccls. and 901/\$.ccls. and 294/\$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/22 09:18
2	1	mounting near apparatus and blow\$2 and 29/\$.ccls. and 414/\$.ccls. and 901/\$.ccls. and 294/\$.ccls.	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/22 09:18
3	0	mounting near apparatus and vacuum near blow and 29/\$.ccls. and 414/\$.ccls. and 901/\$.ccls. and 294/\$.ccls.	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/22 09:19
	7971	component near holding apparatus and blow adj device	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/21 15:49
	2	component adj holding near apparatus and blow adj device	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/21 15:50
	14	component adj holding near apparatus and (29/740; 29/832 ; 29/759 ; 29/743 ; 29/741 ; 29/834 ; 29/836 ; 29/703).ccls.	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:51
-	2	component adj holding and blow near device and (29/740; 29/832 ; 29/759 ; 29/743 ; 29/741 ; 29/834 ; 29/836 ; 29/703).ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:52
-	2	component adj holding and blow\$3 near device and (29/740; 29/832 ; 29/759 ; 29/743 ; 29/741 ; 29/834 ; 29/836 ; 29/703).ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:53
-	3	component adj (mounting or holding) and blow\$3 near device and (29/740; 29/832 ; 29/759 ; 29/743 ; 29/741 ; 29/834 ; 29/836 ; 29/703).ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/07/21 15:59
-	3	6298547.pn.	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 16:04

.

	40	/UAC240F0U UAT020CFU UATT 47 47 1	Hena	0004/07/04
•	10	("4624050" "4703965" "4754545" "4852247" "5207558" 187777244"	USPAT	2004/07/21
		"4852247" "5307558" "5727311"		16:00
		"5745241" "5761798" "5960534"		
_	7	"6161886").PN. ("3921971" "4703965" "4705311"	USPAT	2004/07/21
•	1	(3921971 4703965 4705311 "4729713" "4860438" "4950011"	USPAI	16:01
		"5755471").PN.		10:01
_	3	apparatus and first adj blow near device and	USPAT;	2004/07/21
-	3	second adj blow near device	US-PGPUB:	16:05
		second adj blow hear device	EPO; JPO;	10.05
			DERWENT;	
			IBM_TDB	
_	3	first adj blow near device and second adj	USPAT;	2004/07/21
		blow near device	US-PGPUB;	16:05
			EPO; JPO;	
			DERWENT;	
			IBM_TDB	
-	7	first adj blow near device and second adj	USPAT;	2004/07/21
		blow	US-PGPUB:	16:06
			EPO; JPO;	
			DERWENT;	
			IBM TDB	
_	212	first adj blow and second adj blow and	USPAT;	2004/07/21
		apparatus	US-PGPUB;	16:06
	•		EPO; JPO;	
			DERWENT;	
			IBM_TDB	
-	6	first adj blow and second adj blow and	USPAT;	2004/07/21
		apparatus and 29/\$.ccls.	US-PGPUB;	16:07
			EPO; JPO;	
			DERWENT;	
			IBM_TDB	
-	11	blow near device and apparatus and	USPAT;	2004/07/21
		29/\$.ccls.	US-PGPUB;	16:21
			EPO; JPO;	
			DERWENT;	
	_		IBM_TDB	
•	4	blow adj device near apparatus	USPAT;	2004/07/21
			US-PGPUB;	16:23
			EPO; JPO;	
			DERWENT;	
_	72	blow adj device and mounting	IBM_TDB	2004/07/21
-	"2	biow auj device and mounting	USPAT;	16:28
			US-PGPUB; EPO; JPO;	10.20
]		DERWENT;	
	!			
			IRM TOR	
•	4	blow adi device and mounting near	IBM_TDB USPAT:	2004/07/24
	4	blow adj device and mounting near	USPAT;	2004/07/21 16:30
	4	blow adj device and mounting near component	USPAT; US-PGPUB;	2004/07/21 16:30
-	4	-	USPAT;	

-	512	mounting near apparatus and blow\$2 and	USPAT;	2004/07/21
		devices	US-PGPUB;	16:31
			EPO; JPO;	
			DERWENT;	
			IBM_TDB	
	76	mounting near apparatus and blow\$2 same	USPAT;	2004/07/22
		devices	US-PGPUB;	09:17
			EPO; JPO;	
			DERWENT:	
			IBM TDB	

	Title	Current OR
1	Apparatus for holding component, and apparatus for mounting component	29/740
2	Apparatus for holding component, apparatus for mounting component, and method for mounting component	29/740
3	Electric component transferring apparatus having function of testing negative-pressure suction, and apparatus and method for testing negative-pressure suction	73/37

•

	Current XRef
1	29/743; 294/64.1
2	29/743; 29/832; 29/834
3	29/743; 29/834; 294/64.1; 414/225.01; 414/752.1; 73/37.6; 901/40

3 , ₄